
StainTools Documentation

Release 0.1.0

Peter Byfield

May 18, 2018

Contents

1	Install	3
2	Example usage	5
3	Docs	7
4	Contents	9
4.1	Normalization	9
4.2	Utils	12
5	Indices and tables	15
	Python Module Index	17

Tools for stain normalization and augmentation in Python (tested on 3.5). GitHub repository [here](#).

Latest build:

CHAPTER 1

Install

```
pip install staintools
```

Note: StainTools requires the SPAMS (SPArse Modeling Software) package. Please find out about this [here](#). This may be easily installed via conda. For example, see [here](#).

CHAPTER 2

Example usage

Please see `demo.ipynb` [here](#).

CHAPTER 3

Docs

Made with Sphinx and Read the Docs [here](#).

CHAPTER 4

Contents

4.1 Normalization

4.1.1 Abstract base classes

Normalizer abstract base classes

```
class staintools.normalization.normalizer_abc.FancyNormalizer(**kwargs)
Abstract class for a 'fancy' normalizer (inherits from Normalizer). Adds methods for stain matrix and source concentration estimation.
```

fetch_target_stains()

Fetch the target stain matrix and convert from OD to RGB. Must call fit first (this builds the stain matrix).

Returns

fit(target)

Fit to a target image.

Parameters **target** – Target image RGB uint8.

Returns

static get_concentrations(I, stain_matrix, lambda=0.01)

Get the concentration matrix. Suppose the input image is H x W x 3 (uint8). Define Npix = H * W. Then the concentration matrix is Npix x 2 (or we could reshape to H x W x 2). The first element of each row is the Hematoxylin concentration. The second element of each row is the Eosin concentration.

We do this by ‘solving’ $OD = C*S$ (Matrix product) where OD is optical density (Npix x 3), C is concentration (Npix x 2) and S is stain matrix (2 x 3). See docs for spams.lasso.

We restrict the concentrations to be positive and penalise very large concentration values, so that background pixels (which can not easily be expressed in the Hematoxylin-Eosin basis) have low concentration and thus appear white.

Parameters

- **I** – Image. A np array HxWx3 of type uint8.
- **stain_matrix** – a 2x3 stain matrix. First row is Hematoxylin stain vector, second row is Eosin stain vector.

Returns The Nx2 concentration matrix, where N=H*W is number of pixels.

get_stain_matrix(I, *args)

Estimate stain matrix given an image and relevant method parameters

hematoxylin(I)

Hematoxylin channel extraction.

Parameters **I** – Image RGB uint8.

Returns

transform(I)

Transform an image.

Parameters **I** – Image RGB uint8.

Returns

class staintools.normalization.normalizer_abc.**Normaliser**(**kwargs)

Abstract base class for normalizers. Defines some necessary methods to be considered a normalizer.

fit(target)

Fit the normalizer to an target image

transform(I)

Transform an image to the target stain

4.1.2 Reinhard method

class staintools.normalization.reinhard.**ReinhardNormalizer**(**kwargs)

Normalize a patch stain to the target image using the method of: E. Reinhard, M. Adhikhmin, B. Gooch, and P. Shirley, ‘Color transfer between images’, IEEE Computer Graphics and Applications, vol. 21, no. 5, pp. 34–41, Sep. 2001.

fit(target)

Fit to a target image

Parameters **target** – Image RGB uint8.

Returns

get_mean_std(I)

Get mean and standard deviation of each channel.

Parameters **I** – Image RGB uint8.

Returns

static lab_split(I)

Convert from RGB uint8 to LAB and split into channels.

Parameters **I** – Image RGB uint8.

Returns

static merge_back(I1, I2, I3)

Take seperate LAB channels and merge back to give RGB uint8.

Parameters

- **I1** – L
- **I2** – A
- **I3** – B

Returns Image RGB uint8.

transform(I)

Transform an image.

Parameters **I** – Image RGB uint8.

Returns

4.1.3 Macenko method

class staintools.normalization.macenko.**MacenkoNormalizer**(**kwargs)

Stain normalization based on the method of: M. Macenko et al., ‘A method for normalizing histology slides for quantitative analysis’, in 2009 IEEE International Symposium on Biomedical Imaging: From Nano to Macro, 2009, pp. 1107–1110.

fit(target)

Fit to a target image.

Parameters **target** – Image RGB uint8.

Returns

static get_stain_matrix(I, beta=0.15, alpha=1)

Get the stain matrix (2x3). First row H and second row E. See the original paper for details.

Parameters

- **I** – Image RGB uint8.
- **beta** –
- **alpha** –

Returns

transform(I)

Transform an image.

Parameters **I** – Image RGB uint8.

Returns

4.1.4 Vahadane method

class staintools.normalization.vahadane.**VahadaneNormalizer**(**kwargs)

Stain normalization inspired by method of: A. Vahadane et al., ‘Structure-Preserving Color Normalization and Sparse Stain Separation for Histological Images’, IEEE Transactions on Medical Imaging, vol. 35, no. 8, pp. 1962–1971, Aug. 2016.

static get_stain_matrix(I, threshold=0.8, lambda=0.1)

Get 2x3 stain matrix. First row H and second row E. See the original paper for details. Also see spams docs.

Parameters

- **I** – Image RGB uint8.

- **threshold** –
- **lamda** –

Returns

4.2 Utils

4.2.1 Visualization Utils

Visualization utilities.

`staintools.utils.visual.build_stack(images)`

Build a stack of images from a tuple/list of images.

Parameters `images` – A tuple/list of images.

Returns

`staintools.utils.visual.patch_grid(ims, width=5, sub_sample=False, rand=False, save_name=None)`

Display a grid of patches.

Parameters

- `ims` – A patch ‘stack’
- `width` – Images per row.
- `sub_sample` – Should we take a subsample?
- `rand` – Randomize subsample?

Returns

`staintools.utils.visual.read_image(path)`

Read an image to RGB uint8. Read with opencv (cv) and convert from BGR colorspace to RGB.

Parameters `path` – The path to the image.

Returns RGB uint8 image.

`staintools.utils.visual.show(image, now=True, fig_size=(10, 10))`

Show an image (np.array). Caution! Rescales image to be in range [0,1].

Parameters

- `image` –
- `now` – plt.show() now?
- `fig_size` – Figure size.

Returns

`staintools.utils.visual.show_colors(C)`

Visualize rows of C as colors (RGB)

Parameters `C` – An array N x 3 where the rows are considered as RGB colors.

Returns

4.2.2 Misc Utils

Other utilities.

`staintools.utils.misc.OD_to_RGB(OD)`

Convert from optical density (OD_RGB) to RGB $\text{RGB} = 255 * \exp(-1*\text{OD_RGB})$

Parameters `OD` – Optical denisty RGB image.

Returns Image RGB uint8.

`staintools.utils.misc.RGB_to_OD(I)`

Convert from RGB to optical density (OD_RGB) space. $\text{RGB} = 255 * \exp(-1*\text{OD_RGB})$.

Parameters `I` – Image RGB uint8.

Returns Optical denisty RGB image.

`staintools.utils.misc.array_equal(A, B, eps=1e-09)`

Are arrays A and B equal?

Parameters

- `A` – Array.
- `B` – Array.
- `eps` – Tolerance.

Returns True/False.

`staintools.utils.misc.check_image(x)`

Check if is an image. If gray make sure it is ‘squeezed’ correctly.

Parameters `x` – Input.

Returns True/False.

`staintools.utils.misc.is_gray_image(x)`

Is x a gray image?

Parameters `x` – Input.

Returns True/False.

`staintools.utils.misc.is_image(x)`

Is x an image? i.e. numpy array of 2 or 3 dimensions.

Parameters `x` – Input.

Returns True/False.

`staintools.utils.misc.is_uint8_image(x)`

Is x a uint8 image?

Parameters `x` – Input.

Returns True/False.

`staintools.utils.misc.normalize_rows(A)`

Normalize the rows of an array.

Parameters `A` – An array.

Returns Array with rows normalized.

`staintools.utils.misc.notwhite_mask (I, thresh=0.8)`

Get a binary mask where true denotes ‘not white’. Specifically, a pixel is not white if its luminance (in LAB color space) is less than the specified threshold.

Parameters

- **I** – RGB uint 8 image.
- **thresh** – Luminosity threshold.

Returns Binary mask where true denotes ‘not white’.

`staintools.utils.misc.remove_zeros (I)`

Remove zeros in an image, replace with 1’s.

Parameters **I** – An Array.

Returns New array where 0’s have been replaced with 1’s.

`staintools.utils.misc.sign (x)`

Returns the sign of x.

Parameters **x** – A scalar x.

Returns The sign of x in (+1, -1, 0).

`staintools.utils.misc.standardize_brightness (I, percentile=95)`

Standardize brightness.

Parameters **I** – Image uint8 RGB.

Returns Image uint8 RGB with standardized brightness.

CHAPTER 5

Indices and tables

- genindex
- modindex
- search

Python Module Index

S

staintools.normalization.macenko, 11
staintools.normalization.normalizer_abc,
 9
staintools.normalization.reinhard, 10
staintools.normalization.vahadane, 11
staintools.utils.misc, 13
staintools.utils.visual, 12

Index

A

array_equal() (in module staintools.utils.misc), 13

B

build_stack() (in module staintools.utils.visual), 12

C

check_image() (in module staintools.utils.misc), 13

F

FancyNormalizer (class in stain-
tools.normalization.normalizer_abc), 9

fetch_target_stains() (stain-
tools.normalization.normalizer_abc.FancyNormalizer
method), 9

fit() (staintools.normalization.macenko.MacenkoNormalizer
method), 11

fit() (staintools.normalization.normalizer_abc.FancyNormalizer
method), 9

fit() (staintools.normalization.normalizer_abc.Normaliser
method), 10

fit() (staintools.normalization.reinhard.ReinhardNormalizer
method), 10

G

get_concentrations() (stain-
tools.normalization.normalizer_abc.FancyNormalizer
static method), 9

get_mean_std() (staintools.normalization.reinhard.ReinhardNormalizer
method), 10

get_stain_matrix() (stain-
tools.normalization.macenko.MacenkoNormalizer
static method), 11

get_stain_matrix() (stain-
tools.normalization.normalizer_abc.FancyNormalizer
method), 10

get_stain_matrix() (stain-
tools.normalization.vahadane.VahadaneNormalizer
static method), 11

H

hematoxylin() (staintools.normalization.normalizer_abc.FancyNormalizer
method), 10

I

is_gray_image() (in module staintools.utils.misc), 13

is_image() (in module staintools.utils.misc), 13

is_uint8_image() (in module staintools.utils.misc), 13

L

lab_split() (staintools.normalization.reinhard.ReinhardNormalizer
static method), 10

M

MacenkoNormalizer (class in stain-
tools.normalization.macenko), 11

merge_back() (staintools.normalization.reinhard.ReinhardNormalizer
static method), 10

N

Normaliser (class in stain-
tools.normalization.normalizer_abc), 10

normalize_rows() (in module staintools.utils.misc), 13

notwhite_mask() (in module staintools.utils.misc), 13

O

OD_to_RGB() (in module staintools.utils.misc), 13

P

patch_grid() (in module staintools.utils.visual), 12

R

ReinhardNormalizer (class in stain-
tools.normalization.reinhard), 10

read_image() (in module staintools.utils.visual), 12

remove_zeros() (in module staintools.utils.misc), 14

RGB_to_OD() (in module staintools.utils.misc), 13

S

show() (in module `staintools.utils.visual`), 12
show_colors() (in module `staintools.utils.visual`), 12
sign() (in module `staintools.utils.misc`), 14
`staintools.normalization.macenko` (module), 11
`staintools.normalization.normalizer_abc` (module), 9
`staintools.normalization.reinhard` (module), 10
`staintools.normalization.vahadane` (module), 11
`staintools.utils.misc` (module), 13
`staintools.utils.visual` (module), 12
standardize_brightness() (in module `staintools.utils.misc`), 14

T

transform() (`staintools.normalization.macenko.MacenkoNormalizer`
method), 11
transform() (`staintools.normalization.normalizer_abc.FancyNormalizer`
method), 10
transform() (`staintools.normalization.normalizer_abc.Normaliser`
method), 10
transform() (`staintools.normalization.reinhard.ReinhardNormalizer`
method), 11

V

`VahadaneNormalizer` (class in `staintools.normalization.vahadane`), 11